

SPECIFICATION FEATURES

- Optical System:** Patented field adjustable multi-focal optical system adaptable to a broad range of lighting applications. Outer reflector is Injection Molded Prismatic Acrylic. Inner reflector is fluted, specular aluminum. Adjusting mechanism includes adjustment scale to assist in accurate field-adjustment.
- Housing:** Heavy gauge, die-cast aluminum with heat-dissipation fins and integral splice-compartment. Cast Aluminum hook with safety clasp included.
- Ballast:** Electronic High Frequency. 3.5KV starting pulse with strike limiter. High Power Factor. Integral fusing. 100% factory tested after assembly.
- Source:** Pulse Start Metal Halide, for Vertical, Open-Rated operation, with internal Quartz shroud around arc-tube, clear envelope standard. (Lamp ordered separately).
- Socket:** Mogul Exclusionary Base (EX39). Porcelain, with "pink" glaze. Nickel-plated brass screwshell. Open rated, requiring extended-pin open-rated lamp.
- Finish:** White polyester powder coat.
- Listing:** UL Listed, suitable for damp locations. 50°C ambient.



Electronic Ballast, Acrylic Reflector

NOTE: Assembled and shipped by a U.L. certified supplier. Made in USA

ORDERING INFORMATION

①	②
ACHE	PSM VS
Family	Wattage Source Voltage Options

Please quote the catalog number (Cat. No.) by specifying the appropriate (1 & 2)

① **WATTAGE 200 = 200 Watts**
250 = 250 Watts

② **OPTIONS:**
Cord:
CB3 = 3 ft. Black Cord CW3 = 3 ft. White Cord
CB6 = 6 ft. Black Cord CW6 = 6 ft. White Cord
CB8 = 8 ft. Black Cord CW8 = 8 ft. White Cord

Plugs (Twist Lock)
P61 = (NEMA L6-15P) P71 = (NEMA L7-15P)
P62 = (NEMA L6-20P) P72 = (NEMA L7-20P)
P63 = (NEMA L6-30P) P73 = (NEMA L7-30P)

STINGRAY ENERGY SYSTEMS, LLC
 1550 Douglas Drive
 Charleston, IL 61920
 Telephone 847•656•3557
 Fax 217-348-5391
 Web: www.stingrayenergy.com

Project: _____ **Date:** _____
Type: _____ **Email:** _____
Prepared by: _____
Comments/Additional info: