

SPECIFICATION FEATURES

- Optical System:** Patented field adjustable multi-focal optical system adaptable to a broad range of lighting applications. Reflectors are Injection Molded Prismatic Acrylic. Adjusting mechanism includes adjustment scale to assist in accurate field-adjustment.
- Housing:** Heavy gauge, die-cast aluminum. Removable top splice-compartment with cast aluminum hook. 3/4" K.O.'s top and sides.
- Ballast:** Constant Wattage Autotransformer. Copper-wound with laminated steel core. High Power factor with 4K ignitor. 100% factory tested after assembly.
- Source:** Pulse Start Metal Halide, for Vertical, Open-Rated operation, with internal Quartz shroud around arc-tube, clear envelope. (Lamp ordered separately).
- Socket:** Mogul Exclusionary Base (EX39). Porcelain, with "pink" glaze. Nickel-plated brass screwshell. Open rated, requiring extended-pin open-rated lamp.
- Finish:** White polyester powder coat.
- Listing:** UL Listed, suitable for damp locations.



Magnetic Ballast, Acrylic Reflector, Prism Shield

NOTE: Assembled and shipped by a U.L. certified supplier. Made in USA

ORDERING INFORMATION

①	②	③	④
EXCM	Wattage	Source	Voltage
Family	Wattage	Source	Voltage

① WATTAGE:	150 = 150 Watts	350 = 350 Watts
	200 = 200 Watts	400 = 400 Watts
	250 = 250 Watts	450 = 450 Watts
	320 = 320 Watts	

② SOURCE:	PSM = Pulse Start Metal Halide
	CMH = Ceramic Metal Halide

③ VOLTAGE:	MT = Multi-Tap (120, 208, 240, 277)
	TT = Tri-Tap (120, 277, 347)
	480 = 480 Volt
	277 = 277 Volt Lag/Reactor ballast

Please quote the catalog number (Cat. No.) by specifying the appropriate options.

- ④ **OPTIONS:**
- Cord:**
- | | |
|------------------------|------------------------|
| CB3 = 3 ft. Black cord | CW3 = 3 ft. White cord |
| CB6 = 6 ft. Black cord | CW6 = 6 ft. White cord |
| CB8 = 8 ft. Black cord | CW8 = 8 ft. White cord |
- Plugs (Twist-Iok caps)**
- | | |
|---------------------|---------------------|
| P51 = (NEMA L5-15P) | P71 = (NEMA L7-15P) |
| P52 = (NEMA L5-20P) | P72 = (NEMA L7-20P) |
| P53 = (NEMA L6-30P) | P73 = (NEMA L7-30P) |
| P61 = (NEMA L6-15P) | P81 = (NEMA L8-15P) |
| P62 = (NEMA L6-20P) | P82 = (NEMA L8-20P) |
| P63 = (NEMA L6-30P) | P83 = (NEMA L8-30P) |
- SF = Single Fuse (120, 277, 347 volt)
 - DF = Double Fuse (208, 240, 480 volt)
 - QRS = Quartz Restrike (wattage equal or less than HID)
 - Bi-Level Dimming: Consult Factory
- ACCESSORIES:** all field-installed; please order separately
- SCK = Safety Cable Kit

STINGRAY ENERGY SYSTEMS, LLC
 1550 Douglas, Dr
 Charleston, IL 61920
 Telephone 847•656•3557
 Fax: 217-348-5391
 Web: www.stingrayenergy.com

Project: _____ **Date:** _____

Type: _____ **Email:** _____

Prepared by: _____

Comments/Additional info: